



# Reusche & Co.

a division of  
Trans World Supplies, Inc.

# Material Safety Data Sheet

1299 H Street, Greeley, Colorado 80634, USA (970) 346-8577  
Fax: (970) 346-8575 Email: info@reuscheco.com

Issued By: Jon C. Rarick, President

Product Number: 1118B  
Product Name: Dark Brown Transparent  
Firing Temperature: 1050-1080F  
Issue Date: 7/31/2008

Page: 1 of 3

## Section I: General Information

Manufacturer's Name:

Reusche Co. of Trans World Supplies, Inc.

Emergency Telephone Number:

Regulatory Information: (970) 346-8577 (Weekdays 8:00am - 5:00pm MST)

Poision Control: Poisindex (303) 629-1123 (24 hrs)

Manufacturer's Address:

1299 H Street, Greeley, Colorado, 80631, USA

Disclaimer:

Employers should use this information only as a supplement to other information gathered by them, and should make independent judgements of suitability of this information to ensure proper use and protect the health and safety of employees. The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind expressed or implied is made with respect to the information contained herein.

## Section II: Hazardous Ingredients

Name	WT%	TLV	PEL
Alumina (as AL)	0 - 5		10.00 MG AL/CU. M AIR TWA
Borates (as BO)	0 - 6		10.0 MG BO/CU. M AIR TWA
Insol Chromium CPDS (as CR)	0 - 9		1.00 MG CR/CU. M AIR TWA
Iron CPDS (as FE)	0 - 5	10.00 MG FE/CU. M AIR TWA	
Manganese Compounds (as MN)	0 - 5		1.00 MG MN/CU. M AIR TWA
Inorg. Lead CPDS (as PB)	48 - 58		0.05 MG PB/CU. M AIR TWA
Antimony CPDS (as SB)	0 - 5		0.50 MG SB/CU. M AIR TWA
Silica, Quartz (Free, as SI)	0 - 6		10.00 MG SI/CU. M AIR TWA
Zinc CPDS (as ZN)	0 - 5	10.00 MG ZN/CU. M AIR TWA	
Zirconium CPDS (as ZR)	0 - 5		5.00 MG ZR/CU. M AIR TWA

## Section III: Physical Data

Boiling Point: Not Applicable	Specific Gravity (H2O = 1): Approximately 3.5
Vapor Pressure (mm Hg): Not Applicable	Percent Volatile By Volume (%): 0
Vapor Density (Air = 1): Not Applicable	Evaporation Rate (BuAc = 1): Not Applicable

## Section IV: Fire and Explosion Hazard Data

Flash Point: Non-Flammable	PH: Not Applicable	Unusual Fire Explosion Hazards: Toxic fumes may be evolved during a fire
Extinguishing Media: Material will not burn, however use water to cool metal containers down	Solubility in Water: Insoluable	Decomposition Temperature: Not Applicable
Fire Fighting Procedures, Special: None Required	Apperance and Odor: Powder, Odorless	Melting Point: Not Available



# Reusche & Co.

a division of  
Trans World Supplies, Inc.

# Material Safety Data Sheet

1299 H Street, Greeley, Colorado 80634, USA (970) 346-8577  
Fax: (970) 346-8575 Email: info@reuscheco.com

Issued By: Jon C. Rarick, President

Product Number: 1118B

Product Name: Dark Brown Transparent

Firing Temperature: 1050-1080F

Issue Date: 7/31/2008

Page: 2 of 3

## Section V: Health Hazard Data

### Overexposure Effects:

Harmful if inhaled or swallowed. Repeated and prolonged inhalation may cause delayed injury.

### Emergency and First Aid Procedures - Eyes:

Flush eyes with water for at least 15 minutes. Call a physician

### Emergency and First Aid Procedures - Skin:

Wash with mild soap and water. Call a physician.

### Emergency and First Aid Procedures - Ingestion:

If conscious, give large quantities of water or milk. Induce vomiting. Call a physician.

### Emergency and First Aid Procedures - Inhalation:

Remove to fresh air. Call a physician.

### Emergency and First Aid Procedures - Other:

Wash contaminated clothing prior to reuse.

### Overexposure Effects:

If cadmium is listed as a hazardous ingredient then, as noted by the American Conference of Governmental Industrial Hygienists in their publication, 'Documentation of the Threshold Limit Values', repeated and prolonged exposure to cadmium compounds may cause delayed effects involving the respiratory and renal systems.

### Harmful if Inhaled or Swallowed:

As noted in the OSHA lead standard, repeated and prolonged exposures may cause delayed effects involving the blood, gastrointestinal nervous and reproductive systems.

### Notes to Physician:

Use of this product is regulated by the OSHA lead standard (29 CFR 1910.1025). The extensive medical surveillance and worker provisions of this standard should be consulted.

## Section VI: Reactivity Data

Stability: Stable

### Incompatibility (Materials to Avoid) Hazardous Decomposition Products:

If Cadmium Zinc Sulfide or Cadmium Sulfoselenide are listed as a hazardous ingredient, then the product is incompatible with strong oxidizers and acids, and highly toxic and flammable Hydrogen Sulfide Gas can be generated when product is in contact with strong acids.

### Hazardous Polymerization:

Will Not Occur

## Section VII: Spill or Leak Procedures

### Spill Procedures:

Use appropriate protective equipment during clean up. If reportable quantity is exceeded, contact the National Response Center. Vacuum, with H.E.P.A. filter equipped vacuum, or use wet clean-up techniques and place recovered product in a closable container. The dry sweeping of lead containing dusts is a violation of the OSHA lead standard.

### Waste Disposal Methods:

Dispose in accordance with federal, state and local regulations.

## Section VIII: Special Protection Information

### Ventilation:

Use adequate, localized ventilation for all handling operations.

### Protective Gloves:

Rubber gloves recommended

### Eye Protection:

Protect from dust particles. Use safety goggles or glasses.

### Respiratory Protection:

The use of NIOSH approved respirators equipped with dust, fume, and mist H.E.P.A. filter cartridges during all handling operations recommended.

### Other Protective Equipment:

Consult the OSHA lead standard for 'Operation Specific' protective equipment requirements. Take necessary steps to avoid the contamination of footwear worn away from the work place.



# Reusche & Co.

a division of  
Trans World Supplies, Inc.

# Material Safety Data Sheet

1299 H Street, Greeley, Colorado 80634, USA (970) 346-8577  
Fax: (970) 346-8575 Email: info@reuscheco.com

Issued By: Jon C. Rarick, President

Product Number: 1118B

Product Name: Dark Brown Transparent

Firing Temperature: 1050-1080F

Issue Date: 7/31/2008

Page: 3 of 3

## Section IX: Special Precautions

### Handling, Shipping and Storing Precautions:

Avoid breathing dust or mist. Use with adequate localized ventilation. Avoid contact with skin, eyes and clothing. Wash thoroughly after handling, and before eating, drinking, or smoking. Keep away from food and food products. For manufacturing use only. Store in sealed closed containers.

## Section X: Right to Know Information

### Chemical Name

### CAS #

Frit

65997-18-4

C.I. Pigment Brown 33

68186-88-9

### California Proposition 65:

(1) Lead and Lead Compounds are known to the State of California to cause birth defects or reproductive harm. (2) Cobalt oxide is known to the State of California to cause cancer. (3) Silica, crystalline (particles of respirable size) are known to the State of California to cause cancer.

## Section XI: References

Barclays California Code of Regulations.

29 CFR 1910.1000, Z-Tables

ACGIH TLV for Chemical Substances and Physical Agents.

NIOSH Pocket Guide to Chemical Hazards.