



Reusche & Co.

a division of
Trans World Supplies, Inc.

Material Safety Data Sheet

1299 H Street, Greeley, Colorado 80634, USA (970) 346-8577
Fax: (970) 346-8575 Email: info@reuscheco.com

Issued By: Jon C. Rarick, President

Product Number: 51R502
Product Name: Brunett Flesh NL
Firing Temperature: 1150-1400F
Issue Date: 8/4/2008

Page: 1 of 3

Section I: General Information

Manufacturer's Name:

Reusche Co. of Trans World Supplies, Inc.

Emergency Telephone Number:

Regulatory Information: (970) 346-8577 (Weekdays 8:00am - 5:00pm MST)

Poision Control: Poisindex (303) 629-1123 (24 hrs)

Manufacturer's Address:

1299 H Street, Greeley, Colorado, 80631, USA

Disclaimer:

Employers should use this information only as a supplement to other information gathered by them, and should make independent judgements of suitability of this information to ensure proper use and protect the health and safety of employees. The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind expressed or implied is made with respect to the information contained herein.

Section II: Hazardous Ingredients

Name	WT%	TLV	PEL
Alumina (as AL)	0 - 5		10.00 MG AL/CU. M AIR TWA
Bismuth (as BI)	68 - 78		Not Established
Borates (as BO)	0 - 6		10.0 MG BO/CU. M AIR TWA
Insol Chromium CPDS (as CR)	0 - 7		1.00 MG CR/CU. M AIR TWA
Iron CPDS (as FE)	0 - 9	10.00 MG FE/CU. M AIR TWA	
Silica, Quartz (Free, as SI)	0 - 7		10.00 MG SI/CU. M AIR TWA
Titanium (as TI)	0 - 5		10.00 MG TI/CU. M AIR TWA
Zinc CPDS (as ZN)	0 - 8	10.00 MG ZN/CU. M AIR TWA	
Zirconium CPDS (as ZR)	0 - 7		5.00 MG ZR/CU. M AIR TWA

Section III: Physical Data

Boiling Point:	Specific Gravity (H2O = 1):
Not Applicable	Approximately 3.5
Vapor Pressure (mm Hg):	Percent Volatile By Volume (%):
Not Applicable	0
Vapor Density (Air = 1):	Evaporation Rate (BuAc = 1):
Not Applicable	Not Applicable

Section IV: Fire and Explosion Hazard Data

Flash Point:	PH:	Unusual Fire Explosion Hazards:
Non-Flammable	Not Applicable	Toxic fumes may be evolved during a fire
Extinguishing Media:	Solubility in Water:	Decomposition Temperature:
Material will not burn, however use water to cool metal containers down	Insoluable	Not Applicable
Fire Fighting Procedures, Special:	Apperance and Odor:	Melting Point:
None Required	Powder, Odorless	Not Available

Section V: Health Hazard Data



Reusche & Co.

a division of
Trans World Supplies, Inc.

Material Safety Data Sheet

1299 H Street, Greeley, Colorado 80634, USA (970) 346-8577
Fax: (970) 346-8575 Email: info@reuscheco.com

Issued By: Jon C. Rarick, President

Product Number: 51R502
Product Name: Brunett Flesh NL
Firing Temperature: 1150-1400F
Issue Date: 8/4/2008

Page: 2 of 3

Overexposure Effects:

Harmful if inhaled or swallowed. Repeated and prolonged inhalation may cause delayed injury.

Emergency and First Aid Procedures - Eyes:

Flush eyes with water for at least 15 minutes. Call a physician

Emergency and First Aid Procedures - Skin:

Wash with mild soap and water. Call a physician.

Emergency and First Aid Procedures - Ingestion:

If conscious, give large quantities of water or milk. Induce vomiting. Call a physician.

Emergency and First Aid Procedures - Inhalation:

Remove to fresh air. Call a physician.

Emergency and First Aid Procedures - Other:

Wash contaminated clothing prior to reuse.

Overexposure Effects:

If cadmium is listed as a hazardous ingredient then, as noted by the American Conference of Governmental Industrial Hygienists in their publication, 'Documentation of the Threshold Limit Values', repeated and prolonged exposure to cadmium compounds may cause delayed effects involving the respiratory and renal systems.

Harmful if Inhaled or Swallowed:

As noted in the OSHA lead standard, repeated and prolonged exposures may cause delayed effects involving the blood, gastrointestinal nervous and reproductive systems.

Notes to Physician:

Use of this product is regulated by the OSHA lead standard (29 CFR 1910.1025). The extensive medical surveillance and worker provisions of this standard should be consulted.

Section VI: Reactivity Data

Stability: Stable

Incompatibility (Materials to Avoid) Hazardous Decomposition Products:

If Cadmium Zinc Sulfide or Cadmium Sulfo-selenide are listed as a hazardous ingredient, then the product is incompatible with strong oxidizers and acids, and highly toxic and flammable Hydrogen Sulfide Gas can be generated when product is in contact with strong acids.

Hazardous Polymerization:

Will Not Occur

Section VII: Spill or Leak Procedures

Spill Procedures:

Use appropriate protective equipment during clean up. If reportable quantity is exceeded, contact the National Response Center. Vacuum, with H.E.P.A. filter equipped vacuum, or use wet clean-up techniques and place recovered product in a closable container. The dry sweeping of lead containing dusts is a violation of the OSHA lead standard.

Waste Disposal Methods:

Dispose in accordance with federal, state and local regulations.

Section VIII: Special Protection Information

Ventilation:

Use adequate, localized ventilation for all handling operations.

Protective Gloves:

Rubber gloves recommended

Eye Protection:

Protect from dust particles. Use safety goggles or glasses.

Respiratory Protection:

The use of NIOSH approved respirators equipped with dust, fume, and mist H.E.P.A. filter cartridges during all handling operations recommended.

Other Protective Equipment:

Consult the OSHA lead standard for 'Operation Specific' protective equipment requirements. Take necessary steps to avoid the contamination of footwear worn away from the work place.



Reusche & Co.

a division of
Trans World Supplies, Inc.

Material Safety Data Sheet

1299 H Street, Greeley, Colorado 80634, USA (970) 346-8577
Fax: (970) 346-8575 Email: info@reuscheco.com

Issued By: Jon C. Rarick, President

Product Number: 51R502
Product Name: Brunett Flesh NL
Firing Temperature: 1150-1400F
Issue Date: 8/4/2008

Page: 3 of 3

Section IX: Special Precautions

Handling, Shipping and Storing Precautions:

Avoid breathing dust or mist. Use with adequate localized ventilation. Avoid contact with skin, eyes and clothing. Wash thoroughly after handling, and before eating, drinking, or smoking. Keep away from food and food products. For manufacturing use only. Store in sealed closed containers.

Section X: Right to Know Information

Chemical Name	CAS #
Iron Oxide (FE203)	1309-37-1
Iron Oxide Black	1317-61-9
Titanium Oxide (TI02)	13463-67-7
Frit	65997-18-4

California Proposition 65:

(1) Lead and Lead Compounds are known to the State of California to cause birth defects or reproductive harm. (2) Cobalt oxide is known to the State of California to cause cancer. (3) Silica, crystalline (particles of respirable size) are known to the State of California to cause cancer.

Section XI: References

Barclays California Code of Regulations.
29 CFR 1910.1000, Z-Tables
ACGIH TLV for Chemical Substances and Physical Agents.
NIOSH Pocket Guide to Chemical Hazards.