MATERIAL SAFETY DATA SHEET

for end user

SECTION 1- GENERAL INFORMATION:		
Name:	Telephone No.	
UCHIDA OF AMERICA, CORP.	(310)793-2200	
Address	Telephone No. fo	or Information
3535 DEL AMO BLVD, TORRANCE	(800)541-5877	
CA 90503	Date:	AUGUST 9,2005
Trade name: DECOCOLOR #120,130,140,200,300,400,125	5	

SECTION 2- HEALTH HAZARDS:		
Hazardous ingredients	Component (wt %)	
(chemical or common names)		
XYLENE	30.75	
mineral spirits	0.12	
Hydrocarbon	0.0	
nyurocarbon	0.2	
Benzotriazole	0.5	

Usage Precautions:

Shake well with cap on and holding the cap by thumb before each use. Press down on point until color appears. Close cap after use.

Other precautions:

Non-Flammable. Avoid high temperature ((<40 C or 110 F) and fire sources. Keep out of the reach of children. Use in a well ventilated area.

RULES OF ENTRY	EMERGENCY PROCEDURES	SEEK MEDICAL ADVICE
INHALATION	Remove from area of exposure and call a physician	x
EYES	Rinse away thoroughly with plenty of water.	x
SKIN	Wash off with plenty of water and soap.	
INGESTION	Call a physician	x

SECTION 4- REACTIVITY DATA

Stability: stable Incompatability (materials to avoid: n.d Hazardous decomposition products: n.d. Hazardous polymerization: will not occur

SECTION 5 - SPILL OR LEAK PROCEDURES

Steps to be taken in case material is released or spilled: Take up with absorbent materials Waste disposal method: Dispose in accordance with local regulations

SECTION 6-ADDITIONAL INFORMATION

Signs and Symptoms of overexposure: Irritating to skin,eyes & nose. Sore throat and dizziness. Conforms to ASTM D-4236(IN USA)